

TEMPOFLUX 3 direct flush WC valve

Ref. 763BOX-763000

Time flow dual flush 3L/6L, AB system



DESCRIPTION

TEMPOFLUX 3 direct flush WC valve - Ref. 763BOX-763000

TEMPOFLUX 3 waterproof, recessed time flow direct flush valve:
Satin finish stainless steel wall plate 210 x 162mm.

Waterproof recessing housing:

- Collar with waterproof seal.
- Hydraulic connection to the outside and maintenance from the front.
- Adjusts to all types of installation (rails, solid walls, panels).
- Compatible with wall finishes from 10 - 120mm (while maintaining the minimum recessing depth of 93mm).
- Suitable for standard or "pipe-in-pipe" supply.
- Stopcock and flow rate adjustment, activation unit and cartridge are all integrated and accessible from the front.
- TEMPOFLUX 3 F3/4" flush valve is compatible with sea water and grey water.
- Back flow prevention device inside the housing.
- Supplied in 2 kits: secure system flush without sensitive elements.

Soft-touch operation.

AB Anti-blocking system: flush only takes place once the push-button is released.

Dual flush 3L/6L can be adjusted to 2L/4L.

Outlet connection for PVC tube Ø 26/32mm.

Acoustic level complies with European standard EN 12541 (class II acoustic level).



Suitable for Rimless WC pans.

10-year warranty.

Provisional availability 2nd half 2019, please contact the sales office for more details.

TECHNICAL FEATURES

TEMPOFLUX 3 direct flush WC valve - Ref. 763BOX-763000

Connector	F3/4"
Technology	Time flow
Height	210mm
Depth	93-190mm
Width	162mm
Finish	Stainless steel satin finish
Standards and certifications	
Warranty	

ADVANTAGES



Soft-touch operation



Direct flush: no water stagnation



3L/6L dual flush



Waterproof housing, adjustable and modular

