



CAPACITIES:
 DYNAMIC= 11800 LBF.
 STATIC= 22600 LBF.
 MAX. RECOMMENDED DYNAMIC LOAD= 9400 LBF.
 MAX. RECOMMENDED STATIC LOAD = 15100 LBF.

OUTER RING - MATERIAL: SAE 8620 STEEL
 BLACK OXIDE ALL SURFACES OF OUTER RING

PREPACKED WITH STA-PLEX PREMIUM RED E.P. GREASE

DO NOT SCALE DRAWING
 UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
 INCH DECIMAL :
 INCH FRACTIONAL :
 MILLIMETER (mm) :
 ANGLES :

**RBC DOUBLE ROW
 PITCHLIGN BEARING**
 www.rbcbearings.com

E									
D									
C									
B	01MAY14	CUST. NO.	M	WBG	DWN BY	CHK BY	APP BY	MATERIAL	
A	01FEB23	MARKING ADDED	M	WBG	H.B.		W.B.G.	HEAT TREAT	
REV	DATE	WAS	CHG	APP	92OCT21		92OCT21	SCALE	
ROLLER BEARING COMPANY OF AMERICA, WEST TRENTON, NJ								FULL	FILE NO SJ74\DSJ75241SS10