

<image>

Lightweight 1" Impacts
High Torque



Maintenance

People. Passion. Performance.





PERFECT CONTROL Double stage trigger

SUPER LIGHT : 17 LBS - 7.7 KG Less fatigue thanks to an aluminum housing **GREAT HANDLING** Ergonomic handle with soft touch grip and variable positions

RUGGED Integrated protective cover

UNIVERSAL & DURABLE Twin hammer mechanism

ERGONOMIC & INTUITIVE

COMFORT

Down exhaust blows air away from the operator

Air Cons.@ Load

23.4

23.4

cfm 49.8

49.8

Heavy vehicle tire changing General mechanical works Light industrial maintenance

Powerful
1700 ft.lbs 2320 Nm
of maximum toraue in reverse

Π	2	F	F	Π	
\mathbf{U}	\mathbf{U}			9	

4 positions power setting in both directions and on both sides of the tool


Forward & reverse lever

I	Model	Part #	Impact Mechanism	Anvil	Free Speed	Working) Torque	Max T	orque	We	ight	Ler	ngth	Avg Consui	
I				in	RPM	ft.lbs	Nm	ft.lbs	Nm	lbs	kg	in	mm	cfm	l/s
1	CP7780	894 107 7800	Twin hammer	1'' short	5000	260-1400	350-1900	1700	2320	15	6.8	13.2	335	12	5.6
I	CP7780-6	894 107 7806	Twin hammer	1'' ext. 6"	5000	260-1400	350-1900	1700	2320	17	7.7	19.3	490	12	5.6



SAFE Socket retainer ring combined with hole retainer

Applications







Over 110 years of experience

Since 1901 the Chicago Pneumatic name has represented highperformance tools and equipment designed for an extensive range of applications.

Today, Chicago Pneumatic has a global reach, with local customer centers around the world. Chicago Pneumatic tools and air compressors are tailored to the needs of the industrial, vehicle service, and construction markets. Every day we develop and manufacture new products that are meant to meet your demands not only today, but tomorrow as well. To learn more about our extensive range of tools, hydraulic attachments, industrial and portable compressors, accessories and workshop equipment, please visit www.cp.com.

SPARES & ACCESSORIES

TUNE-UP & REPAIR KITS

MODEL	TUNE-UP KIT	REPAIR KIT
CP7780	894 016 9518	10 kits available see parts list

MODEL		CP7780	CP7780-6	
А	in.	13.2	19.3	
A	mm	335	490	
В	in.	6.7	6.7	
В	mm	171	171	
C =	in.	3.9	3.9	
Ø max	mm	100	100	



DIMENSIONS

IMPACT SOCKET SETS

Part #	Model #	Туре	Pcs.	Dimensions
894 016 4476	SS818	Standard metric	8	27,30,32,33,35,36,38,41mm
894 016 6016	SS814D	Deep metric	4	27,32,33,36mm
894 016 6017	SS818D	Deep metric	8	27,30,32,33,35,36,38,41mm
894 016 7877	SS8107WS	Wheel service metric	7	5 deep: 27,33,35,36,41mm – 2 square: 17,21mm
894 016 4478	80822	Standard SAE	8	7/8",15/16",1",1-1/16",1-1/8",1-3/16",1-1/4",1-1/2"
894 016 4479	SS808D	Deep SAE	8	7/8",15/16",1",1-1/16",1-1/8",1-3/16",1-1/4",1-1/2"
894 016 7876	SS8208WS	Wheel service metric & SAE	8	3 std: 7/8",1",33mm. 3 deep: 1-1/16",1-1/8",1-1/4". 1 square:13/16". Controlled depth: 1-1/2".
894 016 6943	SS8205WS	Wheel service metric & SAE	5	Deep: 33mm, 1-1/2", TW 1-1/8", 1-1/4", Square: 13/16"
894 016 6939	SS8210HDW	Wheel service metric & SAE	10	Deep: 33mm, 1", 1-3/16",1-3/4" TW, DP 1-1/16", 1-1/8",1-1/4" Controlled depth: DP1-1/2",sq.13/16",15/16"

FILTER-REGULATOR-LUBRICATORS

PART # NPT	PART# BSP	SIZE	TYPE		FLOW ATE
				cfm	l/sec
894 016 8519	894 016 8483	3/4"	2 stage	220	100
894 016 8220	894 016 8484	3/4"	2 stage	220	100

More references available in the CP Maintenance Catalog

OPERATOR ACCESSORIES

PART#	DESCRIPTION
Gloves	
894 015 8618	Impact glove size large
894 015 8619	Impact glove size X-large





www.cp.com