



Part Technical Information

User: SCHADC

Page 1

P/N : 791415880

Valid

Filtre double 40bar
Double filter 40bar
Doppelfilter 40bar

created 30/07/14
by: SCHMITT
Updated 10/07/17 Last Revision #E0575
by: SCHMITT

Family:1410 Filter / double filter

Description	Double filter 40bar
Material	Cast iron / carbon steel
Meshmaterial/meshsize	Glass Fiber / 20 microns
Connection	SAE 1"-210bar
Feed direction	one upon another
Maintenance indicator	optic , set point 2 bar
Protection	---
Accessories	2 vents, 4 drains connections
Accessories	without bypass
Type	RFLD ON/PO 111 EAI 20 BM 1.0/-DE-KB
Manufacturer / Supplier	HYDAC

Reference P/N : 791415880

Painting Specifications	: CQF-09
Painting system	: F01
final color	: RAL 5017
Mask	: ---

Technical text

Duplex Filter with switch over valve
(pressure equalization done by switch over valve)
Normal Operating Temperature : -10 to +100°C
Design Pressure/Temperature: 40 bar for -10°C to +100°C
Design Pressure/Temperature: 20 bar for -30°C to +100°C

Materials:

- Body/cover: cast Iron EN-GJS-400-15
- Seals: NBR

Connections (each are plugged) :

- 2 Vents : 1/2"G (upside)
 - 2 Drains (dirty side) : 1/2"G (downside)
 - 2 Drains (clean side) : 1/4"G (downside)
-