VAISALA

Comparison table of HUMICAP® Humidity and Temperature Transmitter HMD60Y and HUMICAP® Humidity and Temperature Transmitter HMD62







FEATURES	Current HMD60Y	New HMD62
Mechanical footprint	Body 100x100x62 mm	101x101x49 mm fits same mounting holes
Probe length	250 mm	250 mm
Materials	Aluminum body Stainless steel probe Chrome plated plastic filter	Aluminum body Stainless steel probe Stainless steel filter
Output signals	2x 4 20 mA floating current loops 0100%RH -20 +80°C	2x 4 20 mA floating current loops Default scale: O100%RH -20 +80°C Configurable with Insight software
Calculated parameters	None	Selectable by DIP: Dew point, Wet bulb, Enthalpy, Absolute humidity, Mixing ratio
Measurement accuracy at room temperature	RH: ±2%RH 0 90%RH T: ± 0.2°C	RH: ±1.5%RH 0 90%RH T: ± 0.1°C
Operating temperature range	-20 +80°C (probe) -20 +60°C (body)	-40 +80°C (probe+ body)
Field adjustment	Trimmers	Trimmers HM70 Insight software
Humidity only model	Available: HMD60U humidity only HMD60T temperature only	Temperature output is always included. Powering of temperature output is optional. Temperature only model TMD62 available

FEATURES	Current HMD60Y	New HMD62
Ingress protection class	IP65 IP6X = Dust tight IPX5= Water jets	IP66 and NEMA4X IP6X = Dust tight IPX6= Powerful water jets
Humidity sensor	HUMICAP®180	Latest HUMICAP*R2 for improved corrosion resistance

HMD60 dimensions









Ref. B211747EN-A ©Vaisala 2018