

Dust Extractor 42L M- Class

VC4210MX/2

Wet and Dry M-Class Dust Extractor with power take-off

Class M - Removes 99.9% of dust with Limit Value for occupational exposure $> 0.1 \text{ mg/m}^3$.

Suitable for processes involving mica, china clay, gypsum, wood dust, such as softwood and hardwood and silica dust, such as masonry, concrete.

Dust Extractor 42L M-Class



TECHNICAL SPECIFICATIONS

Power take-off wattage 1800 w 4.5 m³/min Max Airflow 30 litres **Dust Bag Capacity** Max Sealed Suction 25 kPa Tank Capacity 42 litres Tank capacity Wet 29 litres Input Wattage 1200 w Net weight 16 kg

USER BENEFITS

- Approved for Dust Classes M in accordance with the EU standard.
- · Automatic filter cleaning system.
- Durable PTFE filter with high filtration efficiency.
 Washable non-stick membrane
- Flat top design for deposit of hand tools and accessories.
- Hatchback with big opening for easy access to filter
- Individual settings for different hose diameters (21,27,32, 36 and 38mm)
- Speed regulation
- Air flow sensor beeps when air flow is reduced by clogged filter, full tank etc.
- Automatic On/Off function: machine activates when a connected power tool is used.
- Integrated hose, cable and accessory storage
- Double-wall container with big wheels and steel castors.
- Makpac cases can be attached to the unit with optional adapter plate



Link to product - www.makitauk.com

RELATED PRODUCTS

(Reco

OTHER