

References

SIRCOVER AC I-0-II

Rating (A)	No. of poles	Switch body	Direct handle	External handle	Shaft for external handle	Bridging bars	Auxiliary contact	Terminal shrouds	Terminal screens			
125 A	3 P	41AC 3013	J2 type Blue 1122 1111 Red 1123 1111	S2 type Black IP55 1421 2113 Black IP65 1423 2113 ⁽¹⁾	200 mm 1400 1020 320 mm 1400 1032 ⁽¹⁾	4109 0019	1 st /2 nd contact NO/NC 4109 0021 ⁽²⁾	3 P 2694 3014 ⁽³⁾⁽⁴⁾ 4 P 2694 4014 ⁽³⁾⁽⁴⁾	3 P 1509 3012 4 P 1509 4012			
	4 P	41AC 4013										
160 A	3 P	41AC 3016								4109 0025	3 P 2694 3021 ⁽³⁾⁽⁴⁾ 4 P 2694 4021 ⁽³⁾⁽⁴⁾	3 P 1509 3025 4 P 1509 4025
	4 P	41AC 4016										
200 A	3 P	41AC 3020				4109 0039		3 P 2694 3051 ⁽³⁾⁽⁴⁾ 4 P 2694 4051 ⁽³⁾⁽⁴⁾	3 P 1509 3063 ⁽⁵⁾ 4 P 1509 4063 ⁽⁵⁾			
	4 P	41AC 4020										
250 A	3 P	41AC 3025				4109 0050				3 P 1509 3080 ⁽⁵⁾ 4 P 1509 4080 ⁽⁵⁾		
	4 P	41AC 4025										
315 A	3 P	41AC 3031				4109 0063		3 P 1509 3160 ⁽⁵⁾ 4 P 1509 4160 ⁽⁵⁾				
	4 P	41AC 4031										
400 A	3 P	41AC 3039				4109 0080			3 P 1509 3180 ⁽⁵⁾ 4 P 1509 4180 ⁽⁵⁾			
	4 P	41AC 4039										
500 A	3 P	41AC 3050				4109 0120		3 P 1509 3200 ⁽⁵⁾ 4 P 1509 4200 ⁽⁵⁾				
	4 P	41AC 4050										
630 A	3 P	41AC 3063				4109 0160			3 P 1509 3250 ⁽⁵⁾ 4 P 1509 4250 ⁽⁵⁾			
	4 P	41AC 4063										
800 A	3 P	41AC 3080	4109 0160	3 P 1509 3320 ⁽⁵⁾ 4 P 1509 4320 ⁽⁵⁾								
	4 P	41AC 4080										
1000 A	3 P	41AC 3100	4109 0160		3 P 1509 3350 ⁽⁵⁾ 4 P 1509 4350 ⁽⁵⁾							
	4 P	41AC 4100										
1250 A	3 P	41AC 3120	4109 0160	3 P 1509 3380 ⁽⁵⁾ 4 P 1509 4380 ⁽⁵⁾								
	4 P	41AC 4120										
1600 A	3 P	41AC 3160	4109 0160		3 P 1509 3410 ⁽⁵⁾ 4 P 1509 4410 ⁽⁵⁾							
	4 P	41AC 4160										
1800 A	3 P	41AC 3180	4109 0160	3 P 1509 3440 ⁽⁵⁾ 4 P 1509 4440 ⁽⁵⁾								
	4 P	41AC 4180										
2000 A	3 P	41AC 3200	4109 0160		3 P 1509 3470 ⁽⁵⁾ 4 P 1509 4470 ⁽⁵⁾							
	4 P	41AC 4200										
2500 A	3 P	41AC 3250	4109 0160	3 P 1509 3500 ⁽⁵⁾ 4 P 1509 4500 ⁽⁵⁾								
	4 P	41AC 4250										
3200 A	3 P	41AC 3320	4109 0160		3 P 1509 3530 ⁽⁵⁾ 4 P 1509 4530 ⁽⁵⁾							
	4 P	41AC 4320										

(1) Standard.

(2) 2 pieces supplied, one for position I and one for position II.

(3) To fully shroud front, rear, top and bottom 4 references required.

(4) To shroud front switch top and bottom 2 references required.

(5) 2 pieces supplied, one for top side and another for bottom side.

(6) See "Copper bar connection kits" page 335.