

TORWEGGE

TORsten



MOVE IT FOR TOMORROW

www.torwegge.de

// facts and figures

	autonomous		remote	
	190er	300er*	190er	300er*
Length	1285	ca. 1850	1285	ca. 1850
Width	835	ca. 1300	835	ca. 1300
Height	235	ca. 350	235	ca. 350
Speed	bis zu 1,5 m/s			
own weight	250 kg	630 kg	220 kg	600 kg
Direct Load capacity	1200 kg	3000 kg	1200 kg	3000 kg
Sliding load	2200 kg	7500 kg	2200 kg	7500 kg
Batteries	Lead crystal			
Charging concept I	Connector / Cable			
Charging concept II	Contact			
Charging concept III	inductive			
Drive	SEW 350 W Engines	SEW 3000 W Engines	SEW 350 W Engines	SEW 3000 W Engines
Wheel	190 mm Mecanum	300 mm Mecanum	190 mm Mecanum	300 mm Mecanum
Lifting height	60 mm	60 mm	60 mm	60 mm

* in construction



IFOY AWARD
International forklift truck
of the year 2017

strong
flexible
reliable
powerful
helpful

The word cloud looks like a job description. And TORsten from TORWEGGE ticks all the boxes. It offers unrivalled flexibility, as it can be equipped with a wide range of load platforms and is designed for omnidirectional transport. TORsten is a team player, as it assists its co-workers in performing their tasks through exceptional strength, manoeuvrability, load capacity and ergonomic design. If the layout of the factory or warehouse is modified, there are no additional changes required to the vehicle guiding system, as the TORsten navigates through the room based on a 2D layout of its working area. Customisable energy concepts and a sophisticated safety system make the TORsten not only highly reliable but also cost-efficient.



// Navigation

After transmission of the destination, the TORsten automatically finds the best route to that position by autonomous navigation. For this purpose, the following software components are integrated at the core of the control system in the navigation computer:

- **Localisation**
- **Global route planning**
- **Local collision avoidance**



The **localisation** software is based on the widely used, highly reliable Adaptive Monte Carlo Localisation. Through a fuse of sensors, the data from the laser scanners, the integrated inertia measuring device (rotary speed/acceleration) and the wheel encoders is brought together and to determine the actual global position of the platform. The data from the laser scanners (2D light section) is compared with the factory layout, so that operators can track the position of the platform.



The **global route planning** system refers to a virtual route network that can be configured to reflect the actual physical environment. This approach does away with linear guide systems, inductive loops or magnetic track guide systems. The global route is calculated by means of an A* algorithm, based on the travelled track.



Local collision avoidance makes sure that moving obstacles are reliably identified by the lasers. For this purpose, the planners devise what is known as local cost maps. These maps are constantly updated to show all local obstacles so that the shortest obstacle-free route from the current location to the destination can be calculated. The vehicle is therefore permitted to leave the initially chosen global route should this be necessary to prevent a collision.



The motor and gear system are enclosed in a sturdy industrial drive box from SEW Eurodrive and can withstand heavy mechanical loads. The drive power booster, the motors and the gear system are maintenance-free IP 65 units suitable for operation in demanding industrial environments.



// drive and control concept

The modular power management and control technology of the TORsten meets the requirements of modern autonomous robot vehicles.

48 V DC power system; control voltage 24 V (industry standard)

- 48 V DC intermediate circuit with voltage and current monitor
- Energy supply through inductive power transmission or contacts
- Modern power storage system with environmentally friendly lead crystal batteries
- Operating time of minimum one shift without any need for recharging
- Integrated power management system from SEW Eurodrive

Modular control system for manual remote control or autonomous navigation with integrated route mapping processor

- User-friendly remote control with integrated safety technology for manual control
- Movement range in autonomous mode secured by safety scanners
- Automatic adjustment of vehicle speed to suit working area
- Speed-controlled scanned range switching for accurate movement in confined spaces
- Display of all vehicle parameters and states on stationary monitor

Distinct and consistent robot layer model for software and vehicle control (doing away with first navigation computer layer in the attached vehicle)

- Route planning system
- Robot kinematics (SEW Eurodrive/ MOVI-PLC)
- Multi motion (SEW Eurodrive/ MOVI-PLC)
- Drive power booster (SEW Eurodrive/ ELVCD)
- Drive units (SEW Eurodrive– CMP servomotors)





**Torwegge Intralogistics
GmbH & Co. KG**
Oldermanns Hof 6
33719 Bielefeld

Phone: +49 (0)52193417 – 0
Fax: +49 (0)521 93417 – 611

www.torwegge.de
info@torwegge.de



TORsten Microsite
<http://torsten.torwegge.de>

